

## L-DW Series



### Dry Wall Access Doors

**Doors** are ideally suited for new installations or for remodeling in masonry, tile, wood or other wall and ceiling surfaces. Door features rounded safety corners.

**Door and Frame** are fabricated from 16 gauge, galvanized steel with a white prime coat finish.

**Frame** is one piece construction, 1" wide and provides perfect concealment of the rough wall opening. Wall frame is provided with 1/4" mounting holes for fastening within the furred spaces allowing faster installation and fixing maximum clearance.

**Concealed Pivoting Rod Hinge** prevents distortion and closes door squarely. Doors 24" or larger are provided with a continuous piano hinge.

**Latch** is screwdriver operated.

**Finish** is a white prime coat suitable for painting.

### Guide Specification

Provide Larsen's<sup>®</sup> L-DW Series, Dry Wall Access Doors (Specify model number and options.) Access door and frame shall be fabricated from 16 gauge, galvanized steel with a white prime coat finish. The door shall have rounded safety corners and a concealed pivoting rod hinge. Frame shall be one piece construction with no miters or welds on the face. Latch shall be screwdriver operated. Finish shall be a white prime coat suitable for painting.



## MODEL NUMBER AND OPTIONS SELECTION

### BASE MODEL NUMBER

- L-DW Dry Wall Access Door  
(16 Gauge Steel)

### Suffix Options

- AKL Allen Key Latch  
 - CL Cylinder Lock (one per door)  
 - CLD Cylinder Lock with Dust Shutter (one per door)  
 - MAS Masonry Anchor Straps  
 - MLP Mortise Cylinder Lock (Prep)  
 - SS Stainless Steel Construction (Type 304 No. 4 Satin Finish)  
 - TH 'T' Handle



## STANDARD AVAILABLE SIZES

Special sizes available upon request.

### NOMINAL

#### DOOR SIZE

(WXH)	WALL OPENING	LATCHES	WEIGHT
L-DW 6" x 6"	6-1/2" x 6-1/2"	1	3 lbs.
L-DW 8" x 8"	8-1/2" x 8-1/2"	1	3 lbs.
L-DW 8" x 12"	8-1/2" x 12-1/2"	1	4 lbs.
L-DW 10" x 10"	10-1/2" x 10-1/2"	1	4 lbs.
L-DW 12" x 12"	12-1/2" x 12-1/2"	1	5.5 lbs.
L-DW 12" x 16"	12-1/2" x 16-1/2"	1	6 lbs.
L-DW 12" x 18"	12-1/2" x 18-1/2"	2	6.5 lbs.
L-DW 12" x 24"	12-1/2" x 24-1/2"	3	9.5 lbs.
L-DW 14" x 14"	14-1/2" x 14-1/2"	1	6 lbs.
L-DW 14" x 20"	14-1/2" x 20-1/2"	3	8 lbs.
L-DW 14" x 24"	14-1/2" x 24-1/2"	3	15 lbs.
L-DW 15" x 15"	15-1/2" x 15-1/2"	1	6.5 lbs.
L-DW 16" x 16"	16-1/2" x 16-1/2"	1	7.5 lbs.
L-DW 16" x 20"	16-1/2" x 20-1/2"	3	8.5 lbs.
L-DW 16" x 24"	16-1/2" x 24-1/2"	3	10 lbs.
L-DW 18" x 18"	18-1/2" x 18-1/2"	3	9 lbs.
L-DW 18" x 24"	18-1/2" x 24-1/2"	5	12 lbs.
L-DW 18" x 36"	18-1/2" x 36-1/2"	6	16 lbs.
L-DW 20" x 20"	20-1/2" x 20-1/2"	3	11 lbs.
L-DW 20" x 24"	20-1/2" x 24-1/2"	5	13 lbs.
L-DW 20" x 30"	20-1/2" x 30-1/2"	5	15 lbs.
L-DW 22" x 22"	22-1/2" x 22-1/2"	3	12 lbs.
L-DW 22" x 30"	22-1/2" x 30-1/2"	5	16 lbs.
L-DW 22" x 36"	22-1/2" x 36-1/2"	6	22 lbs.
L-DW 24" x 24"	24-1/2" x 24-1/2"	3	15 lbs.
L-DW 24" x 30"	24-1/2" x 30-1/2"	5	17 lbs.
L-DW 24" x 36"	24-1/2" x 36-1/2"	6	20.5 lbs.
L-DW 24" x 48"	24-1/2" x 48-1/2"	7	28 lbs.
L-DW 30" x 30"	30-1/2" x 30-1/2"	7	21.5 lbs.
L-DW 30" x 36"	30-1/2" x 36-1/2"	8	29 lbs.
L-DW 32" x 32"	32-1/2" x 32-1/2"	7	23 lbs.
L-DW 36" x 36"	36-1/2" x 36-1/2"	8	31.5 lbs.
L-DW 36" x 48"	36-1/2" x 48-1/2"	9	42 lbs.
L-DW 48" x 48"	48-1/2" x 48-1/2"	11	58 lbs.



### NOTES:

1. CONCEALED PIVOTING ROD HINGE
2. DOOR
3. FRAME
4. SCREWDRIVER OPERATED LATCH
5. MOUNTING HOLES

**WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Call Larsen's Manufacturing Co. for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Larsen's assumes no responsibility for use of void or superseded data. © Copyright Larsen's Manufacturing Co.®, Member of Morris Group International® Please visit [www.larsensmfg.com](http://www.larsensmfg.com) for most current specifications.

### SELECTION SUMMARY & APPROVAL FOR MANUFACTURING

Model Number & Options _____	Quantity _____
Company _____	Date _____
Contact _____	Title _____
Approval for Manufacturing/Signature _____	

**L-DW**

Revised: 04/04/2019